

L-Trim SOL

4" Round
Downlight

Project	Type
Catalog Number	



Description

For a downlight application in new construction or retrofit application, USLED provides the L-Trim SOL. Designed to meet any downlight requirements by being offered in four different diameters ranging from 4" – 8" diameter profiles. With the versatility of the fit, the L-Trim SOL is of a durable construction and includes an integrated trim ring in a singular, assembled piece. The L-Trim SOL is included with both an Edison Base and GU24 socket adapters to accommodate any circumstance.

Features

- Compatible with most 4" recessed housings
- Easy installation with adjustable torsion springs
- Integrated trim
- Durable construction
- Edison Base and GU24 socket adaptors included
- Dimmable via Mark 7 (0-10V) dimming interface
- 5-year warranty

Certifications

- UL Listed - New Construction (# E344008)
- UL Listed - Retrofit (# E352453)
- Energy Star Approved



Energy Data

	2700K	3500K	4000K	5000K
Input Voltage (VAC)	120-277	120-277	120-277	120-277
System Level Power (W)**	8.1	8.1	8.1	8.1
Delivered Lumens (Lm)	700	730	730	780
System Efficacy (Lm/W)**	86	90	90	96
Color Temperature (K)	2700	3500	4000	5000
Color Rendering Index (CRI)	80 min	80 min	80 min	80 min
L70 Calculated Life (Hrs)*	>200,000	>200,000	>200,000	>200,000
Operating Temp (°C)	-30 to 45	-30 to 45	-30 to 45	-30 to 45

* US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.

* Measured at 277VAC

Specifications

Dimensions (in)	5" x H2.5"
Units / Carton	1
Net Weight	0.64 lbs
Environmental Rating	Dry

Fixture Ordering Information

Example: LTR2-1-UNV-27-8-4R-V-WH

Series	Variant	CCT		CCT		Power		Size		Mount		Color	
LTR2	1	UNV	120-277	27	2700K	8	8W	4R	4" Round	V	V-Spring (Retrofit)	WH	White
				35	3500K					C	Clamp (New Construction)		
				40	4000K								
				50	5000K								