

VersaQube2

Multi-Purpose Luminaire
1-Qube w/PS

Project	Type
Catalog Number	

Description

For interior or exterior accent lighting applications in new construction or retrofit opportunities, US LED advises the VersaQube2. The VersaQube2 is the ultimate utility light in terms of adaptability. A VersaQube2 can be mounted as a flood light one day, then as a general downlight the next day, due to the directionally modifiable light engine. With all components fully enclosed within an IP65 construction, the VersaQube2 can handle any task, anywhere.



Features

- Powered by a constant current power supply to achieve maximum efficiency
- IP65 ingress protection
- Designed to meet Class 2 safety requirements
- 5-year warranty

Certifications

- UL Listed USA and Canada (# E338791)
- DesignLights Consortium qualified
- LM-79 Test Report available



Energy Data

Input Voltage (VAC)	120-277
System Level Power (W)**	48
Delivered Lumens (Lm)	4,740
System Efficacy (Lm/W)**	98
Color Temperature (K)	5000K
Color Rendering Index (CRI)	70 min
L70 Calculated Life (Hrs)*	>200,000
L85 Calculated Life (Hrs)*	>200,000
Operating Temp (°C)	-30 to 50

* US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.

** Measured at 277VAC

Specifications

Dimensions (in)	11.7" x 7.2" x 4.3"
Units / Carton	1
Net Weight	8.5 lbs
Environmental Rating	Wet

Fixture Ordering Information

Example: VQ2-1-UNVL-12-40

Series	Color	Input Voltage	Light Distribution Pattern	Color Temp
VQ2	1 Bronze	UNVL 120-277	12 2M 5M	40 4000K